



 Print  Copy  Scan  Fax  Publish

Treats every project
as a priority.



KM-2560/KM-3060

The KM-2560 and KM-3060 incorporate extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-2560 and KM-3060 provide effective productivity and maximise uptime whilst ensuring a minimum impact on the environment.

General

Technology: Kyocera Laser, Mono component
Engine speed:
 KM-2560: Max. 25/12.5 pages per minute A4/A3
 KM-3060: Max. 30/15 pages per minute A4/A3
Resolution: 600 x 600 dpi (copy), 1,800 dpi level x 600 dpi (copy, photo mode), Fast 1200 dpi quality (print)
Time to first copy:
 KM-2560/KM-3060: 4.7 seconds or less
Warm-up time: 29 seconds or less from power on
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 560 W, Stand-by: 160 W, Power-Saving (ECOpower): 8.7 W
Noise (ISO 7779): KM-2560: Printing/Copying: 64.7 dB(A) KM-3060: Printing/Copying: 66.5 dB(A)
 Stand-by: 47 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 570 x 620 x 767.2 mm
Weight: Main unit: Approx. 75 kg
Certifications: TÜV/GS, CE, ISO 15408 (under evaluation)
 This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.
Input capacity: 2 x 500-sheet universal paper feeder, 60-120 g/m², A3-A5R, Folio
 200-sheet multi-purpose tray, 45-200 g/m², A3-A6R, Folio, envelopes Max. input capacity with options: 2,200 sheets. Duplex as standard supports A3-A5, 60-80 g/m²
Output capacity: 250 sheets face-down

Copy functions

Max. original size: A3
Continuous copying: 1-999
Memory capacity: Standard 512 MB (max. 1 GB) + 80 GB HDD (system shared)
Zoom range: 25-400% in 1% steps (with DP-670: 25-200%)
Preset magnification ratios: 5R / 5E
Digital features: Interrupt output job, scan once print many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, box image overlay, margin shift, border erase
Exposure mode: Auto, manual: 7 or 13 steps
Image adjustments: Text + photo, text, photo

Print Functions

Processor: PowerPC 750Cxr / 400 MHz
Memory: Standard 512 MB (max. 1 GB) + 80 GB HDD (system shared)
Emulations: PCL6 incl. PjL, KPDL 3 (PostScript 3 compatible) Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, KC-GL, PDF direct print
Controller language: PRESCRIBE

Fonts: 80 outline fonts (PCL6), PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
 Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Features: eMPS – for quick copy, proof and hold, private print, job storage and job management functionality
Interfaces
Standard interface: USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, Fast Ethernet 10-Base-T/ 100Base-TX, CF slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Scan Options

Functionality: Scan-to-SMB/FTP, scan-to-email, scan-to-BOX, (BOX TWAIN)
Scan speed: 50 originals per minute in b/w (300 dpi/A4), 15 originals per minute in colour (300 dpi/A4)
 30 originals per minute in b/w (600 dpi/A4), 15 originals per minute in colour (600 dpi/A4)
Scan resolution: 600, 400, 300, 200, 200 x 400, 200 x 100 dpi (256 greyscales, 256 colour)*
Max. scan size: A3
Original recognition: Text, photo, text + photo, OCR
Interface: 10Base-T/100Base-TX
Network protocol: TCP/IP
File types: Mono: TIFF, PDF. Colour: JPEG, PDF, TIFF (JPEG)
Compression format: B/W: G4 (MMR), Colour: JPEG
Bundle software: KM-NET Viewer, TWAIN source
 *Colour scanning at resolutions of 400 dpi and above requires additional memory.

Fax functions (optional)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm, SUFine: 600 x 600 dpi
Max. original size: A3
Compression method: JBIG, MMR, MR, MH
Memory: Standard 120 MB (enable fax image back up)
Features: Internet fax, network fax, rotate transmission, confidential, relay and bulletin board transmission delivery to document box

Options

Fax System (M)
Paper handling
DP-670 Document processor: 75 sheets, 45-160 g/m², A3-A5R, Folio (RADF), colour scan

PF-670 Paper feeder: 2 x 500 sheets, 60-120 g/m², A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT

DF-670 Document finisher: Max. 500 sheets A4 or 250 sheets A3, Folio, 60-105 g/m², one position stapling max. 30 sheets A4 or 20 sheets A3

DF-730 Document finisher + AK-670*: Max. 1,000 sheets A4 or 500 sheets A3/B4, 64-128 g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-128 g/m²

JS-670 Job separator: 100 sheets internal job separator, 45-160 g/m², A3-A5R

*Adapter-Kit AK-670 is required for the use of DF-730 document finisher.

Memory
DIMM memory: 512 MB memory, DDR-SDRAM DIMM (100 pin): 2 slots (1 slot empty), max. 1 GB

CompactFlash® card: 1 slot (up to 4 GB) for forms, fonts, logos, macro storage

BU-10 Back up memory: 128 MB for fax box image back up

Security
Data security kit (C)
UG-30: PDF expansion kit (high compression, encryption file) Optional interface for print functions

Others
Platen cover (D)

Consumables

TK-679 Toner-kit: Microfine toner for 20,000 pages with 6% coverage

Select your options to suit your needs:



Australia Sales Enquiries
1300 364 429

Australia Web Address
www.kyoceramita.com.au

New Zealand Web Address
www.kyoceramita.co.nz

Sydney Office
 2 Giffnock Ave
 North Ryde NSW 2113
 Phone: (02) 8023 4100
 Fax: (02) 8023 4189

Melbourne Office
 Unit 2, 993 North Road
 Murrumbeena VIC 3163
 Phone: (03) 9579 1555
 Fax: (03) 9579 1544

Brisbane Office
 Cnr Forbes St & Riverside Drive
 West End QLD 4101
 Phone: (07) 3844 6686
 Fax: (07) 3844 8569

Perth Office
 104 Walters Drive
 Osborne Park WA 6017
 Phone: (08) 9201 9155
 Fax: (08) 9201 9511

Adelaide Office
 53 Rundle Street,
 Kent Town SA 5067
 Phone: (08) 7421 2000
 Fax: (08) 7421 2001

Canberra Office
 Epicorp Centre
 401 Clunies Ross Street
 Acton ACT 2601
 Phone: (02) 6229 1729
 Fax: (02) 6229 1701

New Zealand Office
 1-3 Parkhead Place
 Albany New Zealand
 Phone: (64) 9 415 4517
 Fax: (64) 9 415 4597

ABN 77 003 852 444

Kyocera is the Official Supporter of Business Clean Up Day

A SMART ENVIRONMENTAL CHOICE

Protection of the environment is integral to Kyocera's day-to-day operations. Research over the last few decades has been focused, not only developing the most advanced document management devices, but also doing so in harmony with the environment.



ECOSYS devices are designed to minimise both direct costs and indirect costs, such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.



In an effort to reduce future landfill pollution Kyocera has removed 6 hazardous materials from our latest products. Kyocera has implemented a totally lead free manufacturing process using lead free solder and components.



Disclaimer

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to print. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.